

ECOSOFT ROBUST MINI REVERSE OSMOSIS FILTER

APPLICATION: Cafes, petrol stations, offices, schools, stores, etc.



KEY FEATURES

- Flow rate 60 liters per hour
- Made to run 20 hours per hour
- Recovery rate 50% - filter is economical and environmentally-friendly
- Ready-to-install design with pre-installed cartridges and membrane elements
- CE marked and confirmed to be safe by EC New Approach Directives

SPECIFICATION

Code	Flow capacity ¹ , LPH (GPH)	Water consumption, LPH (GPH)	Power supply	Power consumption, kW (hp)	Dimensions, H x W x D, mm (in)
ROBUST1000STD	55-60 (15-16)	110-125 (29-32.6)	110-240 V, 50-60 Hz	0.08 0.12	563 x 382 x 200 (22.2 x 15 x 7.9)

¹At 25 °C feed water temperature, TDS 1000 ppm

SYSTEM COMPONENTS:

- Assembled filter
- Pre-filters and post-filter
- Reverse osmosis membranes
- Feed adapter
- Drain saddle
- Feed valve
- Set of tubes and fittings
- Service wrenches

FILTRATION STAGES:

- 5 micron PP sediment filter 2.5"×10"
- CTO carbon pre-filter 2.5"×10"
- CTO carbon post-filter 2.5"×10"
- Ecosoft membrane elements (3 pc.) 1.8"×12"

ECOSOFT ROBUST MINI REVERSE OSMOSIS FILTER

Code	Product	Membrane	Pieces on pallet
ROBUST1000STD	Direct flow RO Ecosoft ROBUST Mini	3 x CSV1812100ECO	24

ROBUST MINI REPLACEMENT FILTERS

Code	Description	Replacement/ months	Quantity, pcs
CHV3ECO	Ecosoft advanced pack of replacement filters 1-2-3	3	1
CSV1812100ECO	Ecosoft 100 GPD membrane element	12	3

HOW IT WORKS?

